



Polar diagram



Cone diagram



UGR diagram

Glare evaluation according to UGR										
ρ	Ceiling	70	70	50	50	30	70	70	50	50
ρ	Walls	50	30	50	30	30	50	30	50	30
ρ	Floor	20	20	20	20	20	20	20	20	20
Room size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	18.4	19.6	18.7	19.8	20.1	19.9	21.1	20.2	21.3
	3H	19.4	20.5	19.7	20.7	21.0	21.1	22.2	21.4	22.4
	4H	19.8	20.8	20.1	21.1	21.3	21.5	22.6	21.9	22.8
	6H	20.0	20.9	20.3	21.2	21.5	21.8	22.8	22.2	23.1
	8H	20.0	20.9	20.4	21.2	21.6	21.9	22.8	22.2	23.1
	12H	20.0	20.9	20.4	21.2	21.6	21.9	22.8	22.3	23.1
4H	2H	19.0	20.0	19.4	20.3	20.6	20.2	21.2	20.6	21.5
	3H	20.2	21.0	20.5	21.4	21.7	21.6	22.5	22.0	22.8
	4H	20.6	21.4	21.0	21.7	22.1	22.2	22.9	22.6	23.3
	6H	20.9	21.6	21.3	22.0	22.4	22.6	23.2	23.0	23.6
	8H	21.0	21.6	21.4	22.0	22.4	22.7	23.3	23.1	23.7
	12H	21.1	21.6	21.5	22.0	22.4	22.7	23.3	23.2	23.7
8H	4H	20.9	21.5	21.3	21.9	22.3	22.3	22.9	22.7	23.3
	6H	21.3	21.7	21.7	22.2	22.6	22.7	23.2	23.2	23.7
	8H	21.4	21.8	21.9	22.3	22.7	22.9	23.3	23.4	23.8
	12H	21.5	21.8	21.9	22.3	22.8	23.0	23.4	23.5	23.8
12H	4H	20.9	21.4	21.3	21.8	22.3	22.3	22.8	22.7	23.2
	6H	21.3	21.7	21.8	22.2	22.6	22.7	23.2	23.2	23.6
	8H	21.4	21.8	21.9	22.3	22.8	22.9	23.3	23.4	23.8

Variation of the observer position for the luminaire distances S

S = 1.0H	+0.2 / -0.3	+0.1 / -0.2
S = 1.5H	+0.3 / -0.7	+0.3 / -0.5
S = 2.0H	+0.7 / -1.3	+0.8 / -0.9

Standard table BK04 BK04

Correction summand 1.9 3.4

Corrected glare indices referring to 1071lm Total luminous flux

The UGR values are calculated in acc. with CIE Publ. 117. Spacing-to-Height-Ratio = 0.25