



Polar diagram



Cone diagram



UGR diagram

Glare evaluation according to UGR														
ρ	Ceiling	70	70	50	50	30	70	70	50	50	30			
ρ	Walls	50	30	50	30	30	50	30	50	30	30			
ρ	Floor	20	20	20	20	20	20	20	20	20	20			
Room size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis								
2H	2H	19.0	20.3	19.3	20.5	20.8	19.3	20.6	19.6	20.8	21.1			
	3H	20.4	21.6	20.7	21.9	22.1	20.8	22.0	21.1	22.3	22.6			
	4H	20.9	22.1	21.3	22.4	22.7	21.4	22.5	21.7	22.8	23.1			
	6H	21.3	22.3	21.6	22.6	23.0	21.8	22.8	22.1	23.1	23.5			
	8H	21.4	22.4	21.7	22.7	23.0	21.9	22.9	22.3	23.2	23.5			
	12H	21.4	22.4	21.8	22.7	23.1	21.9	22.9	22.3	23.2	23.6			
4H	2H	19.6	20.8	20.0	21.1	21.4	19.9	21.0	20.2	21.3	21.6			
	3H	21.2	22.2	21.6	22.5	22.9	21.6	22.6	22.0	22.9	23.2			
	4H	21.9	22.8	22.3	23.1	23.5	22.3	23.1	22.7	23.5	23.9			
	6H	22.3	23.1	22.8	23.5	23.9	22.8	23.5	23.2	23.9	24.3			
	8H	22.5	23.2	22.9	23.6	24.0	22.9	23.6	23.4	24.0	24.4			
	12H	22.5	23.2	23.0	23.6	24.0	23.0	23.6	23.5	24.0	24.5			
8H	4H	22.2	22.9	22.6	23.2	23.7	22.5	23.2	22.9	23.6	24.0			
	6H	22.7	23.3	23.2	23.7	24.2	23.1	23.7	23.6	24.1	24.6			
	8H	22.9	23.4	23.4	23.9	24.3	23.3	23.8	23.8	24.3	24.7			
	12H	23.0	23.4	23.5	23.9	24.4	23.4	23.9	23.9	24.3	24.8			
12H	4H	22.2	22.8	22.6	23.2	23.6	22.5	23.1	23.0	23.5	24.0			
	6H	22.8	23.3	23.2	23.7	24.2	23.1	23.6	23.6	24.1	24.6			
	8H	23.0	23.4	23.5	23.9	24.4	23.4	23.8	23.9	24.3	24.8			
Variation of the observer position for the luminaire distances S														
S = 1.0H	+0.1 / -0.1			+0.1 / -0.1										
S = 1.5H	+0.2 / -0.4			+0.2 / -0.3										
S = 2.0H	+0.5 / -0.8			+0.5 / -0.6										
Standard table	BK05					BK05								
Correction summand	2.7					3.1								
Corrected glare indices referring to 1046lm Total luminous flux														

The UGR values are calculated in acc. with CIE Publ. 117. Spacing-to-Height-Ratio = 0.25