



Polar diagram



Cone diagram



Luminous emittance 1 / UGR diagram

Glare evaluation according to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room size	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
X	Y										
2H	2H	16.8	18.0	17.1	18.2	18.4	18.4	19.6	18.7	19.8	20.0
	3H	17.7	18.8	18.0	19.1	19.3	19.6	20.7	19.9	20.9	21.2
	4H	18.1	19.1	18.4	19.4	19.6	20.0	21.1	20.4	21.3	21.6
	6H	18.3	19.2	18.6	19.5	19.8	20.3	21.3	20.7	21.6	21.9
	8H	18.3	19.2	18.7	19.5	19.8	20.4	21.3	20.8	21.6	21.9
4H	2H	17.4	18.4	17.7	18.7	19.0	18.7	19.7	19.1	20.0	20.3
	3H	18.5	19.4	18.9	19.7	20.0	20.1	21.0	20.5	21.3	21.6
	4H	18.9	19.7	19.3	20.1	20.4	20.7	21.4	21.1	21.8	22.1
	6H	19.2	19.9	19.6	20.2	20.6	21.0	21.7	21.5	22.1	22.5
	8H	19.3	19.9	19.7	20.3	20.7	21.2	21.8	21.6	22.1	22.6
8H	2H	19.3	19.8	19.7	20.3	20.7	21.2	21.7	21.6	22.2	22.6
	4H	19.2	19.8	19.6	20.2	20.6	20.8	21.4	21.2	21.8	22.2
	6H	19.5	20.0	20.0	20.4	20.9	21.2	21.7	21.7	22.1	22.6
	8H	19.6	20.0	20.1	20.5	21.0	21.4	21.8	21.8	22.2	22.7
	12H	19.7	20.0	20.2	20.5	21.0	21.4	21.8	21.9	22.3	22.8
12H	4H	19.2	19.7	19.6	20.1	20.6	20.7	21.3	21.2	21.7	22.1
	6H	19.5	20.0	20.0	20.4	20.9	21.2	21.6	21.7	22.1	22.6
	8H	19.7	20.0	20.2	20.5	21.0	21.4	21.7	21.9	22.2	22.7
Variation of the observer position for the luminaire distances S											
S = 1.0H	+0.2 / -0.3					+0.2 / -0.2					
S = 1.5H	+0.4 / -0.8					+0.3 / -0.5					
S = 2.0H	+0.8 / -1.4					+0.8 / -1.0					
Standard table	BK04					BK04					
Correction summand	0.3					2.0					
Corrected glare indices referring to 666lm Total luminous flux											

The UGR values are calculated in acc. with CIE Publ. 117. Spacing-to-Height-Ratio = 0.25