



Polar diagram



Cone diagram



UGR diagram

| Glare evaluation according to UGR | | | | | | | | | | | | |
|--|--|---|------|------|------|------|--|------|------|------|------|----|
| ρ Ceiling | | 70 | 70 | 50 | 50 | 30 | 70 | 70 | 50 | 50 | 30 | 30 |
| ρ Walls | | 50 | 30 | 50 | 30 | 30 | 50 | 30 | 50 | 30 | 30 | 30 |
| ρ Floor | | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 |
| Room size X Y | | Viewing direction at right angles to lamp axis | | | | | Viewing direction parallel to lamp axis | | | | | |
| 2H | 2H | 22.3 | 23.4 | 22.8 | 24.0 | 24.5 | 20.9 | 22.1 | 21.4 | 22.6 | 23.2 | |
| | 3H | 24.1 | 25.1 | 24.7 | 25.7 | 26.3 | 22.1 | 23.1 | 22.7 | 23.7 | 24.3 | |
| | 4H | 24.9 | 25.9 | 25.5 | 26.5 | 27.1 | 22.6 | 23.5 | 23.1 | 24.1 | 24.8 | |
| | 6H | 25.7 | 26.6 | 26.3 | 27.2 | 27.9 | 22.9 | 23.8 | 23.5 | 24.4 | 25.1 | |
| | 8H | 26.1 | 26.9 | 26.7 | 27.5 | 28.2 | 23.0 | 23.9 | 23.6 | 24.5 | 25.2 | |
| 4H | 12H | 26.4 | 27.3 | 27.0 | 27.9 | 28.6 | 23.0 | 23.9 | 23.7 | 24.5 | 25.2 | |
| | 2H | 22.8 | 23.8 | 23.4 | 24.4 | 25.0 | 21.7 | 22.7 | 22.3 | 23.3 | 23.9 | |
| | 3H | 24.8 | 25.7 | 25.5 | 26.3 | 27.0 | 23.2 | 24.0 | 23.8 | 24.6 | 25.3 | |
| | 4H | 25.9 | 26.6 | 26.5 | 27.2 | 28.0 | 23.8 | 24.6 | 24.5 | 25.2 | 25.9 | |
| | 6H | 26.8 | 27.5 | 27.5 | 28.1 | 28.9 | 24.3 | 25.0 | 25.0 | 25.6 | 26.4 | |
| 8H | 8H | 27.3 | 27.9 | 27.9 | 28.5 | 29.3 | 24.5 | 25.1 | 25.2 | 25.8 | 26.6 | |
| | 12H | 27.7 | 28.3 | 28.4 | 28.9 | 29.7 | 24.6 | 25.2 | 25.3 | 25.9 | 26.6 | |
| | 4H | 26.1 | 26.7 | 26.8 | 27.4 | 28.2 | 24.4 | 25.0 | 25.1 | 25.7 | 26.5 | |
| | 6H | 27.3 | 27.8 | 28.0 | 28.5 | 29.3 | 25.2 | 25.7 | 25.9 | 26.4 | 27.2 | |
| | 8H | 27.9 | 28.4 | 28.6 | 29.1 | 29.9 | 25.5 | 25.9 | 26.2 | 26.6 | 27.5 | |
| 12H | 12H | 28.5 | 28.9 | 29.2 | 29.6 | 30.5 | 25.7 | 26.1 | 26.5 | 26.8 | 27.7 | |
| | 4H | 26.1 | 26.7 | 26.8 | 27.4 | 28.2 | 24.5 | 25.1 | 25.2 | 25.8 | 26.6 | |
| | 6H | 27.4 | 27.8 | 28.1 | 28.6 | 29.4 | 25.4 | 25.8 | 26.1 | 26.6 | 27.4 | |
| | 8H | 28.1 | 28.5 | 28.8 | 29.2 | 30.0 | 25.8 | 26.2 | 26.5 | 26.9 | 27.8 | |
| | Variation of the observer position for the luminaire distances S | | | | | | | | | | | |
| S = 1.0H S = 1.5H S = 2.0H | | +0.1 / -0.1 +0.2 / -0.3 +0.3 / -0.5 | | | | | +0.1 / -0.1 +0.3 / -0.4 +0.4 / -0.9 | | | | | |
| Standard table | | BK08 | | | | | BK06 | | | | | |
| Correction summand | | 11.3 | | | | | 8.2 | | | | | |
| Corrected glare indices referring to 930lm Total luminous flux | | | | | | | | | | | | |

The UGR values are calculated in acc. with CIE Publ. 117. Spacing-to-Height-Ratio = 0.25